

# TEST 701 serial number: 202001

standard wool felt, white for evaluations with rub fastness tester FEK-VESLIC

**generally:**

<b>according:</b>	ISO 11640:2018, VESLIC-C4500, IUF 450
<b>suitable:</b>	for determining the colour fastness
<b>durability:</b>	5 years (minimum)
<b>storing conditions:</b>	must be well packed and kept dark

**specification of material:**

<b>article 701</b>	wool felt, white
<b>base material</b>	wool, 100%
<b>weight</b>	1900 g/m <sup>2</sup> ± 150 g/m <sup>2</sup>
<b>density</b>	0.32 g/cm <sup>3</sup> ± 0.035 g/cm <sup>3</sup> (category F1, DIN 61200)
<b>pH</b>	4.0 – 8.0
<b>thickness</b>	6.0 mm ± 0.5 mm
<b>colour</b>	*colouring compared to a Standard-batch (internal method)

**batch control:**

<b>appearance</b>	square pieces of white* wool felt, measuring 15 mm x 15 mm, punched out of a sheet of pure wool felt
<b>weight</b>	1878 g/m <sup>2</sup>
<b>density</b>	0.30 g/cm <sup>3</sup>
<b>pH</b>	7.3
<b>thickness</b>	6.1 mm

**wetting time:**

as described in ISO 11640:2018, paragraph 7.2	< 180 seconds
-----------------------------------------------	---------------